

Description

This double-sided tape consists of a paper tissue carrier, layered on both sides with a modified dispersion acrylate adhesive. The adhesive has a high temperature, aging and plasticiser resistance as well as a high adhesive power. This tape is the APEO-free analogon of 1359 with the same very good technical properties like 1359.

Carrier

Paper tissue, 12,7 g/m²

Liner

white silicone-coated paper on both sides, 90 g/m², with blue ORAFOL branding

Adhesive

APEO-free modified dispersion acrylate

Area of use

This tape is especially suitable for the adhesion of cellular rubber and EPDM. Because of its aggressive adhesive it is also appropriate for the adhesion of textiles, wood, open-pore and impregnated foams, cellular polyethylene, soft PVC and other rough, open surfaces.

Technical Data

Thickness* (adhesive and carrier)	160 micron
Temperature resistance***	-40° C to +140° C
Loop tack* (FINAT TM 9)	26 N/25 mm
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min: 23 N/25 mm after 20 min: 25 N/25 mm after 24 h: 27 N/25 mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	at 23° C: > 72 h at 70° C: 30 min
Temperature resistance* (S.A.F.T.)	110° C
Shelf life**	2 years
Application temperature	> +15° C

* average ** in original packaging, at 20°C and 50% relative humidity *** normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.

